



RF9

Access Control

Wireless router

- **Wireless router for SiPass Entro system**
- **Use to extend the radio link from the SR35i and the RF30-EM reader**
- **Acts as a tool for measuring radio coverage**
- **LED for signal strength and communication quality**
- **Battery use for test purposes**

RF9 extends the radio link from the SR35i and the RF30-EM. It also acts as a tool for measuring radio coverage. It includes three LEDs to indicate signal strength and communication quality.

Technical data

RF9	
Battery	For test purposes 9 V. Type: 6LR61
Operating voltage	8 to 30 VAC 8 to 40 VDC
Current consumption	Average: 40 mA Peak: 110 mA (8 VDC)
Frequency band	2.4 GHz
Indicators	3 x LED (red/yellow/green)
Operating temperature	-10 °C to +55 °C
Environment	Indoor use only
IP rating	IP30
Colour	Off-white, RAL9002
Dimensions (Ø x H)	110 x 48 mm (with socket)
Approval	CE

Details for ordering

Type	Part no	Designation	Weight
RF9	S54505-B1-A1	Wireless Router	0.10 kg
RF9	GBI:31-120	Bewator branded Wireless Router	0.10 kg

Issued by
Siemens Building Technologies
Fire & Security Products GmbH & Co. oHG
D-76181 Karlsruhe
www.buildingtechnologies.siemens.com

© 2009 Copyright by
Siemens Building Technologies
Fire & Security Products GmbH & Co. oHG
Data and design subject to change without notice.
Supply subject to availability.